

Pressure

Electronic Pressure Switch

BPS3000

Features

- ▶ Measuring range:
 - Gauge: 0 - 9000 psig
 - Absolute: 0 - 150 psia
- ▶ Suitable for indoor and outdoor usage*
- ▶ One or two switch points
- ▶ 0.50% accuracy
- ▶ Analog output 4 - 20 mA or 0 - 10 V
- ▶ Superior EMI protection
- ▶ Display & electronic connection: rotatable by 320°
- ▶ Simple navigation menu
- ▶ Suitable for rapid cycling applications
- ▶ Hydraulic and pneumatic compatible

Applications

- ▶ Machine tool industry
- ▶ Factory Automation
- ▶ Injection molding machines
- ▶ Lubrication monitoring
- ▶ Pumps and compressors

General Specifications**



Sensor element:	Ceramic sensor (standard) Optional: piezoresistive sensor (For proper sensor selection see product configurator for more details.)
Materials:	
Wetted parts:	304 Stainless steel
Enclosure:	304 Stainless steel/polycarbonate/elastomer/ polyamide
Seals:	FKM fluorelastomer (standard) EPDM (optional)
Operating elements:	3 easy-response push-buttons
Enclosure rating:	Type 4X (IP65) / Type 6 (IP67)
Protection class:	III
Electrical connection:	Plug M12 x 1, 4-pin / 5-pin
Process connection:	1/4" NPT, 1/2" NPT flush diaphragm, 7/16-20 (SAE), 7/16-20 (JIC 37°), G1/4" M, G1/2" flush diaphragm (only piezoresistive)
Dimensions:	1.6 Ø x 4.4 inches (without plug connector)
Weight:	Approx. 0.4 lb (200 g)
Proof pressure:	1.5X rated pressure
A/D-Converter:	
Resolution:	12 bit (4,096 steps per measure span)
Scanning rate:	1000/s
Linearity error:	< ±0.5 % f. s. at +25 °C
Temperature influence:	TC zero < ±0.2 % FSO / 10K TC span < ±0.3 % FSO / 10K
Compensation range:	14°F to 158°F (-10°C to +70°C)
Repeatability:	±0.1% f. s.
Temperature range:	
Media:	-13°F to 212°F (-25°C to +100°C)
Electronics:	14°F to 158°F (-10°C to +70°C)
Storage:	-22°F to 176°F (-30°C to +80°C)
Power supply:	15 to 32 V DC, reversed polarity protected (SELV, PELV) Class 2
Power consumption:	Approx. 50 mA (without load)

Digital display:	4-digit 14-segment LED red display, digit height .35 inches (9 mm)	
Display rate:	20/s	
Error display:	LED RED and alphanumeric display	
Analog output:		
Current output:	4-20 mA	
Scanning rate:	2 ms	
Voltage output:	0 to 10 V DC	
Rating:	max. 10 mA	
Adjustment range:	25% to 100% f. s.	
Transistor switching outputs:		
Switching function	Normally open / normally closed, standard /window mode and diagnosis function adjustable	
Switching output:	PNP	
Adjustment range for switching point and hysteresis:	0% to 125% f. s.	
Switching frequency:	Max. 100 Hz	
Load:	Max. 500 mA, short-circuit-proof	
Delay:	0.0 s to 9.9 s adjustable	
Status display(s):	LED(s) red	
Approvals:	cULus	
EMI	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5-Surge	1/2 kV
	EN 61000-4-6 HF conducted	10 V
	Shock resistance	DIN EN 60028-2-27
Vibration resistance	DIN EN 60028-2-26	20 g (10 to 2000 Hz)

* Unit is made from UV rated materials and UL approved at an IP67 class of ingress protection. LED display may not be easily visible in bright direct sunlight.

** See product configurator for additional options.

Electronic Pressure Switch

BPS3000

Technical Drawings

Connection diagram

Electrical Connection Chart

M12 Pin Call-Out	Models with 2 switching output	Models with 1 switching output and 1 analog output	Models with 2 switching output and 1 analog output
Color Code of Mating Cable	Plug 4-pin	Plug 4-pin	Plug 5-pin
Pin 1 Brown	15 to 32 VDC	15 to 32 VDC	15 to 32 VDC
Pin 2 White	SP2 (500 mA/100 Hz)	Analog Output (500 mA/100 Hz)	Analog Output (500 mA/100 Hz)
Pin 3 Blue	0 V	0 V	0 V
Pin 4 Black	SP1 (500 mA/100 Hz)	SP1 (500 mA/100 Hz)	SP1 (500 mA/100 Hz)
Pin 5 Grey	Not Applicable	Not Applicable	SP2 (500 mA/100 Hz)

Process Connections "A"

Process Connections "A"	Dimension "B"
1/4" NPT	.66" [16.9 mm]
1/2" NPT flush diaphragm seal	.83" [21 mm]
7/16-20 UNF (SAE 4)	.36" [9.1 mm]
7/16-20 UNF (JIC 37°)	.55" [14 mm]
G 1/4"	.47" [12 mm]
G 1/2"	.55" [14 mm]

Dimensions [in inches]

Product Configurator

Example **BPS3** **4** **E** **V** **M** **6000P** **P**

Series:

BPS3 Series BPS3000, electronic dual pressure switch

Output:

1	Dual switch point
2	Single switch point plus 4-20mA
3	Single switch point plus 0-10V
4	Dual switch point plus 4-20mA
5	Dual switch plus 0-10V

Process Connections:

N	1/4" NPT male thread
3	1/2" NPT flush diaphragm seal
E	7/16-20 UNF (SAE 4)
P	7/16-20 UNF male thread (JIC 37°)
G	G1/4" male thread
2	G1/2" flush diaphragm seal
1	40x40 Cetop/Manifold (contact factory)

Sealing:

V	FKM fluorelastomer (standard)
E	EPDM (EPR) (optional)

Electrical Connection:

M¹ M12

Sensor:

Blank	Standard ceramic sensor
P	Piezoresistive sensor

Pressure Ranges²

0015PA ³	0 - 15 psia (absolute)
0075PA ³	0 - 75 psia (absolute)
0150PA ³	0 - 150 psia (absolute)
0003P ³	0 - 3 psig
0015P ³	0 - 15 psig
0050P ³	0 - 50 psig
0075P ³	0 - 75 psig
0150P	0 - 150 psig
0750P	0 - 750 psig
1500P	0 - 1500 psig
3000P	0 - 3000 psig
6000P ³	0 - 6000 psig
9000P ³	0 - 9000 psig

Accessories

Order Number	Description
239535-1M-R-S ⁴	4 Pin M12 Female Right Angle Plug Molded Cable, 3.28 Feet (1 Meter), Shielded
239535-1M-S ⁴	4 Pin M12 Female Straight Plug Molded Cable, 3.28 Feet (1 Meter), Shielded
239537	4 Pin M12 Female Straight Connector
239236	4 Pin M12 Female Right Angle Connector
239546-1M-R-S ⁴	5 Pin M12 Female Right Angle Plug Molded Cable, 3.28 Feet (1 Meter), Shielded
239546-1M-S ⁴	5 Pin M12, Female Straight Plug Molded Cable, 3.28 Feet (1 Meter), Shielded
239548-S	5 Pin M12 Female Straight Connector
239548-R	5 Pin M12 Female Right Angle Connector

Note:

- Mating connector not included with unit; mating connectors are available and can be ordered as an accessory.
- Contact factory for ranges not listed including BAR.
- Pressure range requires piezoresistive sensor.
- See Cable Connectors & Accessories for more options.

Barksdale

3211 Fruitland Avenue • Los Angeles, CA 90058 • ☎ 800-835-1060 • Fax: 323-589-3463 • www.barksdale.com CONTROL PRODUCTS

See Barksdale's Standard Conditions of Sale • Specifications are subject to modification at any time • Bulletin #S0117-A • 07/14 • ©2014 • Printed in the U.S.A.