

# Transducers

## General Industrial Transducer (Amplified)

**Series 423, 425, 426**

### Features

- ▶ General purpose, industrial grade transducer
- ▶ Diffused silicon sensor for high accuracy and reliability
- ▶ Rugged stainless steel enclosure
- ▶ Superior surge voltage protection and EMI/RFI immunity
- ▶ Built-in high pressure snubber (2000 psi and above)
- ▶ Current and voltage signals

### Applications

- ▶ Industrial hydraulic equipment
- ▶ Cranes
- ▶ Compressors
- ▶ Gas metering
- ▶ Vacuum machinery packaging



### General Specifications\*

<b>Accuracy (LH &amp; R):</b>	±0.25% BSL
<b>Long Term Stability:</b>	±0.5% FSO of calibration curve
<b>Typical Life Cycle:</b>	100 million cycles
<b>Proof Pressure:</b>	2 times rated pressure or 13,000 psi max. (884 bar), whichever is less
<b>Input:</b>	
423:	Excitation voltage: 9 to 30 VDC
426:	Excitation voltage: 14 to 30 VDC
425:	Excitation voltage: 12 to 32 VDC
<b>Supply Current:</b>	15 mA maximum (no load)
<b>Min. Load Resistance:</b>	2K ohms (voltage series only)
<b>Output:</b>	
423:	Output: 0.5 to 5.5 VDC Full scale output: 5.0 VDC ± 0.8% Zero output: 0.5 VDC ± 0.4%
426:	Output: 1 to 11 VDC Full scale output: 10 VDC ± 1% Zero output: 1.0 VDC ± 2%
425:	Output: 4 to 20 mA Full scale output: 16 mA ± 1% Zero output: 4 mA ± 2%
<b>Wetted Parts:</b>	17-4 PH & 300 series stainless steel
<b>Enclosure:</b>	NEMA 4, 300 series stainless steel

\* See product configurator for additional options.

### Wiring Code


423, 425 & 426			
T5/H5/T4/H4	T2	H3	
1	A	Red	+ Excitation
3	B	Black	+ Output
2	C	Green	Common
4	D	White	Case Ground
-	-	Bare	Shield

<b>Pressure Connection:</b>	1/4"-18 NPT male (STD)
<b>Response Time:</b>	1 kHz (typ)
<b>Electrical Connection:</b>	3 conductor for voltage series and 2 conductor for current series, 24 awg, PVC jacketed, shielded cable, 3 ft. (1 m) long with integral strain relief and case ground.
<b>Temperature Ranges:</b>	
Operating:	-40° to 185°F (-40° to 85)°C
Compensated:	30° to 160°F (-1° to 71)°C
Storage:	-40° to 185°F (-40° to 85)°C
<b>Temperature Shift:</b>	
Zero & Span:	0.0125% per °F over compensated range, 75°F reference (±1% of FSO over temp. range)
<b>Vibration:</b>	15 g's, 10-2000 Hz, MIL-STD 202
<b>Shock:</b>	50 g's, 11 ms, MIL-STD 202 Method 213, Cond. G.
<b>Built-in Protection:</b>	Conducted & radiated RF emissions/interference to EN 55011  IEC 801-2, -3, -4, -5, and -6  EN/IEC 6100-4-2, -3, -4, -5, -6  Refer to engineering drawing for details.
<b>Weight:</b>	
423 & 426:	7.4 oz. (221 grams) to 1000 psi 9.9 oz. (281 grams) 2,000 psi and higher
425:	7.4 oz. (210 grams) to 1000 psi 9.4 oz. (266 grams) 2,000 psi and higher
<b>Warranty:</b>	3 year warranty

# General Industrial Transducer (Amplified)

# Series 423, 425, 426

## Technical Drawings



## Product Configurator

Example	425	H3	-19	P1	
---------	-----	----	-----	----	--

### Base Model

423	0.5 - 5.5 VDC analog output
425	4 - 20 mA analog output
426	1 - 11 VDC analog output

### Electrical Connection

H3	Shielded & jacketed #22 AWB cable (1 meter) (standard)
H4	Subminiature DIN connector (43650 type) - mating connector included
H5	Shielded & jacketed cable with 1/2" male conduit
T2 <sup>1</sup>	Bendix connector (PT02A-8-4P) - 4 pin
T4 <sup>2</sup>	M12 Hirschman connector (ELST 412 PG9)
T5	Standard DIN connector (43650) - mating connector included

### Pressure Range

-23	0 - 29.9" of Hg
-25	0 - 5 psi (0 - 0.35 bar)
-01	0 - 15 psi (0 - 1 bar) <sup>4</sup>
-21	0 - 30 psi (0 - 2 bar) <sup>4</sup>
-03	0 - 50 psi (0 - 3.5 bar) <sup>4</sup>
-22	0 - 60 psi (0 - 4 bar) <sup>4</sup>
-04	0 - 100 psi (0 - 6.9 bar) <sup>4</sup>
-05	0 - 150 psi (0 - 10.3 bar) <sup>4</sup>
-06	0 - 200 psi (0 - 12.8 bar) <sup>4</sup>
-07	0 - 300 psi (0 - 20.7 bar) <sup>4</sup>
-08	0 - 500 psi (0 - 34.5 bar)
-19	0 - 600 psi (0 - 41 bar)
-10	0 - 1,000 psi (0 - 69 bar)
-11	0 - 1,500 psi (0 - 104 bar)
-12	0 - 2,000 psi (0 - 138 bar) <sup>5</sup>
-13	0 - 3,000 psi (0 - 207 bar) <sup>5</sup>
-14	0 - 4,000 psi (0 - 276 bar) <sup>5</sup>
-15	0 - 5,000 psi (0 - 345 bar) <sup>5</sup>
-16	0 - 6,000 psi (0 - 414 bar) <sup>5</sup>
-17	0 - 7,500 psi (0 - 517 bar) <sup>5</sup>
-18	0 - 10,000 psi (0 - 689 bar) <sup>5</sup>

### Options

-N4X	Nema 4X enclosure (H3 Option only)
-E <sup>6</sup>	External zero span adjustment
-Z15	Calibrated in bars
-Z10	1 to 5V output (available only on 423 models)
-Z11	1 to 6V output (available only on 423 models)
-Z12	0.5 to 4.5V output (available only on 423 models)
-Z16	2 to 10V output (available only on 426 models)
-WXXX	Additional length of free leads (in inches) (H3/H5 connection)
-ZXXY	Special pressure ranges (see note 3)

## Accessories

Order #	Description
23969	Bendix mating connector (T2 electrical option)
239236	Hirschman mating connector (T4 electrical option)
208360	Pressure snubber (1/4-18 NPT female/male)

### Process Connection

Blank	1/4-18 NPT male (standard)
-P1	7/16-20 UNF-2B female
-P3	7/16-20 UNF-2A male

Blank	Gauge pressure
-A	Absolute pressure range (<300psi)

<sup>1</sup> Mating connector: Bendix # PT06E-8-4S or equivalent (not included). Order number: 23969

<sup>2</sup> Mating connector: Hirschman # ELWIKA 4021 PG7 or equivalent (not included). Order number: 239236

<sup>3</sup> Add suffix ZXXY for special pressure ranges. XX = significant digits. Y = number of trailing zeros.

Example: for 230psi callibration, add Z231

<sup>4</sup> Available in absolute ranges

<sup>5</sup> Built-in surge protector

<sup>6</sup> Available with connector options H3 and T4 only.